





Date : December 01, 2020

TECHNICAL SPECIFICATIONS			
Item	Qty	Unit	Description
Single Sheave Prussik Minding Pulley	20	pcs	Multifunctional pulley for block-and-tackle systems for ropes up to 16mm. Aluminum alloy body and wheel, stainless steel axle. Diameter: Minimum Breaking Load: 46kN or above; Meets NFPA or CE EN standards.
Rescue 8 ring (with Horn)	30	pcs	Stainless steel. NFPA or CE and UIAA standards; Breaking Strength (lbs): 11,250 (50kN) or above;
Leather gloves (Rappelling Gloves)	50	pairs	Gloves for work on ropes, in first quality leather. NFPA 1951 or CE EN 388 certification against mechanical risks (protection values: abrasion 4, cutting 1, tearing 3, puncture 3.) Color: Black
D Type Carabiner	50	pcs	CE UIAA EN 362 EN12275 or NFPA G Rated Carbon Steel; MBS: 52KN or above (Major Axis)
Tandem Pulley	6	pcs	Linear double pulley with stainless wheels. Accommodates ropes up to 13mm and steel cables up to 12mm diameter. Max Breaking Load: 20 kN or above
Anchor plate	6	pcs	Strong aluminum alloy plates with multiple anchor holes 45kN or above/8 holes
Kern Mantle Rope (Life Safety Rope)	1000	Meters	Static (Black) 12.5mm x 50M 100% polyester static kernmantle; Certified to NFPA 1983 (G) Minimum MBS Rating:40 kN or above Must not be more than 3 years from date manufacture.
Laid Rope	2000	Meters	Marine Laid Rope 12mm x 220M manufactured from a combination of synthetic fibers: Polypropylene and Polyester.Total Weight: 20.9kg; MBS: 2377kg/ 5240 lbs or above;
Rescue Helmet	50	pcs	Lightweight, ergonomic safety helmet designed for technical activities like rope access, tree climbing and rescue. Certified according to EN12492 or NFPA 1951. Also meets the requirements of energy absorption and resistance to penetration of EN 397. Full strength chin strap (-50kg) prevents incidental or accidental release. Ventilated ABS shell with high density EPS foam on the inside. Equipped with attachment points for ear protection, visor and headlamp. One size fits all. Size 54-62cm. Color: Orange
NOTE:	For Bidding		
End-User:	Approved by:		
			
SFO1 Mark Leonil A Bonzon BRRTU Skills-in-Charge	FSSUPT BELINDA B OCHAVE Director, NFTI		